

PIATTAFORMA DATI ESTERNI

**APPLICAZIONE PDE**

*Implementation Guide*

**INDICE**

Implementation Guide.....	1
1 INTRODUZIONE.....	2
1.1 Scopo del documento.....	2
1.2 Applicabilità.....	2
1.3 Glossario.....	2
2 FORMATO DEGLI SCHEMI.....	2
2.1 TimmBaseMessage.xsd.....	2
2.2 TimmMessage.xsd.....	2
2.3 BaseMessageTypes.xsd.....	2
2.4 RegistrationTypes.xsd.....	2
2.5 Ce_Types.xsd.....	2
3 TRANSAZIONI XML SOTTOMESSE DAGLI OPERATORI A PDE.....	2
3.1 Contratto.....	2
3.1.1 Contratto.xsd.....	2
3.2 ItemContratto.....	2
3.2.1 ItemContratto.xsd.....	2
3.3 QuoteCapacita.....	2
3.3.1 QuoteCapacita.xsd.....	2
4 TRANSAZIONI XML MESSE A DISPOSIZIONE DEGLI OPERATORI.....	2
4.1 FunctionalAcknowledgement.....	2
4.1.1 Functional Acknowledgement Positivo.....	2
4.1.2 Functional Acknowledgement Negativo.....	2
4.1.3 FunctionalAcknowledgement.xsd.....	2
4.2 Notifica di errore (ref xsd: TimmBaseMessage.xsd).....	2

## **1 INTRODUZIONE**

### **1.1 Scopo del documento**

L'Applicazione PDE interagisce con diversi attori utilizzando specifiche transazioni.

Questo documento descrive le transazioni supportate dall'applicazione per scambiare informazioni in ingresso ed in uscita con gli operatori.

### **1.2 Applicabilità**

Questo documento contiene il file Excel che descrive le transazioni XML di scambio dati supportate dall'Applicazione PDE.

### **1.3 Glossario**

PDE: Piattaforma dati esterni

## 2 FORMATO DEGLI SCHEMI

All'interno della presentazione di questa Implementation Guide vengono presentati gli XSD distinti per ogni tipo transazione.

Utilizzando opportunamente l'istruzione "include" è possibile ottenere lo schema *TimmMessage.xsd* (nello schema contenitore *TimmBaseMessage*) che richiama gli xsd specifici di ogni transazione coinvolta nell'applicazione.

Di conseguenza gli esempi indicati nei capitoli successivi mostrano l'xsd della singola transazione e un esempio completo di file XML pronto ad essere inviato alla piattaforma.

## 2.1 TimmBaseMessage.xsd

```

<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-TIMM" xmlns:pd="urn:XML-TIMM"
  elementFormDefault="qualified">
  <include schemaLocation="BaseMessageTypes.xsd" />
  <element name="Message">
    <complexType>
      <sequence>
        <element ref="pd:tyVersion" minOccurs="0" maxOccurs="1" />
        <element name="Header" type="pd:tyHeader" minOccurs="1" maxOccurs="1" />
        <choice>
          <element ref="pd:Transaction" minOccurs="1" maxOccurs="unbounded" />
          <element name="Error" type="pd:tyError" minOccurs="1" maxOccurs="unbounded" />
        </choice>
      </sequence>
      <attribute name="MessageCode" type="pd:tyCeMessageCode" use="optional" />
      <attribute name="MessageType" type="pd:tyMessageType" use="optional" />
      <attribute name="MessageDate" type="date" use="required" />
      <attribute name="MessageTime" type="time" use="optional" />
      <attribute name="MessageSubject" type="pd:tyMessageSubject" use="optional" />
      <!-- Response -->
      <attribute name="ResponseReferenceMessageCode" type="pd:tyMessageCode" use="optional" />
      <attribute name="ResponseMessageStatus" type="pd:tyMessageStatus" use="optional" />
    </complexType>
  </element>
  <element name="TransactionDetail" abstract="true" />
  <element name="Transaction">
    <complexType>
      <choice>
        <element ref="pd:TransactionDetail" minOccurs="1" maxOccurs="1" />
      </choice>
      <attribute name="MPN" type="pd:tyExternalReferenceNumber" use="optional" />
      <!-- Response -->
      <attribute name="ResponseTransactionStatus" type="pd:tyTransactionStatus" use="optional" />
      <attribute name="ResponseProcessingTime" type="dateTime" use="optional" />
      <attribute name="ResponseReferenceTransactionCode" type="pd:tyTransactionCode" use="optional" />
    </complexType>
  </element>
  <element name="tyVersion" abstract="true" type="string" />
</schema>

```

## 2.2 TimmMessage.xsd

```

<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-TIMM"
  xmlns:pd="urn:XML-TIMM"
  xmlns:Namespace1="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">
  <include schemaLocation="TimmBaseMessage.xsd" />
  <include schemaLocation="FunctionalAcknowledgement.xsd" />
  <include schemaLocation="Contratto.xsd" />
  <include schemaLocation="ItemContratto.xsd" />
  <include schemaLocation="QuoteCapacita.xsd" />
  <element name="Version" substitutionGroup="pd:tyVersion" type="string" />
  <element name="TimmFA" substitutionGroup="pd:TransactionDetail">
    <complexType>
      <sequence>
        <element name="FunctionalAcknowledgement" type="pd:tyFunctionalAcknowledgement" />
      </sequence>
    </complexType>
  </element>
  <element name="Contratto" substitutionGroup="pd:TransactionDetail">
    <complexType>
      <sequence>
        <element name="ContrattoCommon" type="pd:tyContrattoCommon" />
      </sequence>
    </complexType>
  </element>
  <element name="ItemContratto" substitutionGroup="pd:TransactionDetail">
    <complexType>
      <sequence>
        <element name="ItemContrattoCommon" type="pd:tyItemContrattoCommon" />
      </sequence>
    </complexType>
  </element>
  <element name="QuoteCapacita" substitutionGroup="pd:TransactionDetail">
    <complexType>
      <sequence>
        <element name="QuoteCapacitaCommon" type="pd:tyQuoteCapacitaCommon" />
      </sequence>
    </complexType>
  </element>
</schema>

```

## 2.3 BaseMessageTypes.xsd

```
<?xml version="1.0" encoding="iso-8859-1" ?>
<schema id="MessageTypes"
xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="urn:XML-TIMM"
xmlns:pd="urn:XML-TIMM"
elementFormDefault="qualified">
<complexType name="tyError">
<attribute name="Code" type="string" use="required" />
<attribute name="Description" type="string" use="required" />
</complexType>
<complexType name="tyHeader">
<sequence>
<element name="Sender" type="pd:tyAddress"/>
<element name="Receiver" type="pd:tyAddress"/>
</sequence>
</complexType>
<complexType name="tyAddress">
<sequence>
<element name="OperatorMsgCode" type="pd:tyOperatorMsgCode"/>
<element name="CompanyName" type="pd:tyCompanyName" minOccurs="0"/>
<element name="UserMsgCode" type="pd:tyUserMsgCode" minOccurs="0"/>
</sequence>
</complexType>
<simpleType name="tyOperatorMsgCode">
<restriction base="string">
<minLength value="1" />
<maxLength value="16" />
</restriction>
</simpleType>
<simpleType name="tyUserMsgCode">
<restriction base="string">
<minLength value="1" />
<maxLength value="16" />
</restriction>
</simpleType>
<simpleType name="tyMessageCode">
<restriction base="string">
<minLength value="32" />
<maxLength value="32" />
</restriction>
</simpleType>
```

## PDE: IMPLEMENATATION GUIDE

```
<simpleType name="tyCeMessageCode">
  <restriction base="string">
    <minLength value="1" />
  </restriction>
</simpleType>
<simpleType name="tyTransactionCode">
  <restriction base="string">
    <minLength value="32" />
    <maxLength value="32" />
  </restriction>
</simpleType>
<simpleType name="tyFreeTransactionCode">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="32" />
  </restriction>
</simpleType>
<simpleType name="tyTransactionStatus">
  <restriction base="string">
    <enumeration value="Accepted" />
    <enumeration value="Rejected" />
  </restriction>
</simpleType>
<simpleType name="tyMessageType">
  <restriction base="string">
    <enumeration value="Request" />
    <enumeration value="Response" />
    <enumeration value="Notify" />
  </restriction>
</simpleType>
<simpleType name="tyMessageSubject">
  <restriction base="string">
    <enumeration value="TransactionTIMMCmd" />
    <enumeration value="TransactionTIMMFA" />
    <enumeration value="TransactionOperator" />
    <enumeration value="TransactionUser" />
    <enumeration value="TransactionUserRelate" />
  </restriction>
</simpleType>
<simpleType name="tyMessageStatus">
  <restriction base="string">
    <enumeration value="Accepted" />
    <enumeration value="Rejected" />
    <enumeration value="PartiallyAccepted" />
  </restriction>
</simpleType>
<simpleType name="tyCompanyName">
```



## PDE: IMPLEMENTATION GUIDE

```
<restriction base="string">  
  <minLength value="1"/>  
  <maxLength value="60"/>  
</restriction>  
  
</simpleType>  
<simpleType name="tyExternalReferenceNumber">  
  <restriction base="string">  
    <minLength value="1"/>  
    <maxLength value="32"/>  
  </restriction>  
</simpleType>  
</schema>
```

## 2.4 RegistrationTypes.xsd

```
<?xml version="1.0" encoding="iso-8859-1" ?>
<schema id="MessageTypes"
xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="urn:XML-TIMM"
xmlns:pd="urn:XML-TIMM"
elementFormDefault="qualified">

  <simpleType name="tyRagioneSociale">
    <restriction base="string">
      <minLength value="0" />
      <maxLength value="256" />
    </restriction>
  </simpleType>

  <simpleType name="tyPartitaIVA">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="50" />
    </restriction>
  </simpleType>

  <simpleType name="tyCodiceFiscale">
    <restriction base="string">
      <minLength value="0" />
      <maxLength value="50" />
    </restriction>
  </simpleType>

  <simpleType name="tyIndirizzo">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="256" />
    </restriction>
  </simpleType>

  <simpleType name="tyCAP">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="50" />
    </restriction>
  </simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyCitta">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="120" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyProvincia">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="2" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyNazione">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyEmail">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="60" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyTelefono">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="60" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyFax">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="60" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyTitolo">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="50" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCognome">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="60" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyNome">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="60" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyUserName">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="128" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyPassword">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="128" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyIssuer">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tySerialNumber">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyReferenteAmministrativo">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tySedeAmministrativa">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyResponsabileAggiornamento">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="255" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyLingua">  
  <restriction base="string">  
    <minLength value="5" />  
    <maxLength value="5" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCIN">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="1" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyABI">  
  <restriction base="string">  
    <minLength value="5" />  
    <maxLength value="5" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCAB">  
  <restriction base="string">  
    <minLength value="5" />  
    <maxLength value="5" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyCC">  
  <restriction base="string">  
    <minLength value="12" />  
    <maxLength value="12" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyIBAN">  
  <restriction base="string">  
    <minLength value="34" />  
    <maxLength value="34" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyAliquotaleVA">  
  <restriction base="int">  
    <minInclusive value="0" />  
    <maxInclusive value="100" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceRuolo">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceUtente">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodicePuntoDiScambioRilevante">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyDescrizionePuntoDiScambioRilevante">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyCoefficienteDiPerdita">
  <restriction base="float">
    <minInclusive value="0.0" />
    <maxInclusive value="1.0" />
  </restriction>
</simpleType>

<simpleType name="tyCodiceZona">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="4" />
  </restriction>
</simpleType>

<simpleType name="tyTipoZona">
  <restriction base="string">
    <enumeration value="PPL" />
    <enumeration value="PHYS" />
    <enumeration value="VIRT" />
  </restriction>
</simpleType>

<simpleType name="tyDescrizioneZona">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="256" />
  </restriction>
</simpleType>

<simpleType name="tyCodiceUnita">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="16" />
  </restriction>
</simpleType>

  <simpleType name="tyNomeUnita">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="100" />
    </restriction>
  </simpleType>
<simpleType name="tyCodiceImpianto">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="20" />
  </restriction>
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyCodiceTipoTecnologia">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="1" />
  </restriction>
</simpleType>

<simpleType name="tyCodiceSottoTipoTecnologia">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="20" />
  </restriction>
</simpleType>

<simpleType name="tyCodiceUdd">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="20" />
  </restriction>
</simpleType>

<simpleType name="tyP_IVA">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="16" />
  </restriction>
</simpleType>

<simpleType name="tyCombustibile">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="8" />
  </restriction>
</simpleType>
```



## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyCodiceProprietario">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceMotivazione">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyDate">  
  <restriction base="integer">  
    <minInclusive value="19000101"/>  
    <maxInclusive value="29001231"/>  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyHourIntervalType">  
  <restriction base="integer">  
    <minInclusive value="1"/>  
    <maxInclusive value="25"/>  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyTipoUnita">  
  <restriction base="string">  
    <enumeration value="C" />  
    <enumeration value="M" />  
    <enumeration value="P" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tySottoTipoUnita">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="100" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyDescrizioneUnita">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceContratto">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="32" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceInvio">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCedenteAcquirente">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="150" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyStrutturaContratto">  
  <restriction base="string">  
    <enumeration value="future"/>  
    <enumeration value="swap"/>  
    <enumeration value="opzione"/>  
    <enumeration value="altro" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyTipologiaContratto">  
  <restriction base="string">  
    <enumeration value="OTC"/>  
    <enumeration value="MKT"/>  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyDescrizioneContratto">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyIndicizzazioneContratto">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyMercatoOrganizzato">  
  <restriction base="string">  
    <minLength value="0" />  
    <maxLength value="256" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyCodiceoperatore">  
  <restriction base="string">  
    <minLength value="1" />  
    <maxLength value="16" />  
  </restriction>  
</simpleType>
```

```
<simpleType name="tyOrdineDiMerito">  
  <restriction base="integer">  
    <minInclusive value="0" />  
  </restriction>  
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyUnbalancedPartecipantNumber">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="60" />
  </restriction>
</simpleType>

<simpleType name="tyInjectionOrWithdrawalPointNumber">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="16" />
  </restriction>
</simpleType>

<simpleType name="tyMustRun">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="256" />
  </restriction>
</simpleType>

  <simpleType name="tyTipoOperatore">
    <restriction base="string">
      <enumeration value="STD" />
      <enumeration value="OWN" />
      <enumeration value="SPC" />
      <enumeration value="TSO" />
      <enumeration value="ANG" />
    </restriction>
  </simpleType>

<simpleType name="tySegno">
  <restriction base="string">
    <enumeration value="+" />
    <enumeration value="-" />
  </restriction>
</simpleType>
</schema>
```

## 2.5 Ce\_Types.xsd

```

<?xml version="1.0" encoding="iso-8859-1" ?>
<schema id="MessageTypes"
xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="urn:XML-TIMM"
xmlns:pd="urn:XML-TIMM"
elementFormDefault="qualified">

  <element name="RejectInformation">
    <complexType>
      <sequence>
        <element name="Reason" type="pd:tyReasonType"/>
        <element name="ReasonText" type="pd:tyReasonTextType" minOccurs="0" maxOccurs="1"/>
      </sequence>
    </complexType>
  </element>

  <simpleType name="tyCodiceOperatore">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="16" />
    </restriction>
  </simpleType>

  <simpleType name="tyAlpha">
    <restriction base="string">
      <pattern value="^[0](, \d{1,2})|^[1](,[0]{1,2})|^[1]$" />
    </restriction>
  </simpleType>

  <simpleType name="tyRendimentoMedio">
    <restriction base="string">
      <pattern value="^\d{1,4}(\, \d{1,4})|^\d{1,4}(\, \d{1,3})|^\d{1,4}(\, \d{1,2})|^\d{1,4}(\, \d{1,1})|^\d{1,4}$" />
    </restriction>
  </simpleType>

  <simpleType name="tyQtyCO2">
    <restriction base="string">
      <pattern value="^\d{1,12}(\, \d{1,4})|^\d{1,12}(\, \d{1,3})|^\d{1,12}(\, \d{1,2})|^\d{1,12}(\, \d{1,1})|^\d{1,12}$" />
    </restriction>
  </simpleType>

```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyQtyCombustibile">
  <restriction base="string">
    <pattern value="^[d{1,12},\d{1,4}]|^?[d{1,12},\d{1,3}]|^?[d{1,12},\d{1,2}]|^?[d{1,12},\d{1,1}]|^?[d{1,12}]$"/>
  </restriction>
</simpleType>

<simpleType name="tyPotenzaMW">
  <restriction base="string">
    <pattern value="^[d{1,12},\d{1,4}]|^?[d{1,12},\d{1,3}]|^?[d{1,12},\d{1,2}]|^?[d{1,12},\d{1,1}]|^?[d{1,12}]$"/>
  </restriction>
</simpleType>

<simpleType name="tyQtyMWh">
  <restriction base="string">
    <pattern value="^[d{1,12},\d{1,3}]|^?[d{1,12},\d{1,2}]|^?[d{1,12},\d{1,1}]|^?[d{1,12}]$"/>
  </restriction>
</simpleType>

<simpleType name="tyPrice">
  <restriction base="string">
    <pattern value="^[d{1,12},\d{1,2}]|^?[d{1,12},\d{1,1}]|^?[d{1,12}]$"/>
  </restriction>
</simpleType>

<simpleType name="tyQtyMWhxxx">
  <restriction base="string">
    <pattern value="^[+]?[d{1,3}](.[d{3}])|^[-+]?[d{1,9}]|^[-+]?[d{1,3}](.[d{3}])^(.[d{3}])|^[-+]?[d{1,9}](.[d{3}])$"/>
  </restriction>
</simpleType>

<simpleType name="tyQtyMWhPos">
  <restriction base="string">
    <pattern value="^[d{1,3}](.[d{3}])|^?[d{1,3}](.[d{3}])^(.[d{3}])|^?[d{1,9}]|^?[d{1,9}](.[d{3}])$"/>
  </restriction>
</simpleType>

<simpleType name="tyQtyMWhNeg">
  <restriction base="string">
    <pattern value="^-?[d{1,3}](.[d{3}])|^-[d{1,3}](.[d{3}])^(.[d{3}])|^-[d{1,9}]|^-[d{1,9}](.[d{3}])$"/>
  </restriction>
</simpleType>

<simpleType name="tyPriceMWh">
  <restriction base="string">
    <pattern value="^[d{1,3}](.[d{3}])|[d{1,3}](.[d{3}])^(.[d{1,2}]|^?[d{1,9}]|^?[d{1,9}](.[d{1,2}])$"/>
  </restriction>
</simpleType>
```

## PDE: IMPLEMENATATION GUIDE

```
</simpleType>
<simpleType name="tyPGMPriceMWh">
  <restriction base="string">
    <pattern value="^\d{1,3}((\d{3})*)\d{1,3}((\d{3})*)(\d{1,6})|^?\d{1,9}|^?\d{1,9}(\d{1,6})$" />
  </restriction>
</simpleType>

<simpleType name="tyControValore">
  <restriction base="string">
    <pattern value="^[+-]?\d{1,3}((\d{3})*)|^[-+]?\d{1,3}((\d{3})*)(\d{1,2})|^[-+]?\d{1,9}|^[-+]?\d{1,9}(\d{1,2})$" />
  </restriction>
</simpleType>

<simpleType name="tyPUN">
  <restriction base="string">
    <pattern value="^\d{1,3}((\d{3})*)\d{1,3}((\d{3})*)(\d{1,6})|^?\d{1,9}|^?\d{1,9}(\d{1,6})$" />
  </restriction>
</simpleType>

<simpleType name="tyUnitOfMeasure">
  <restriction base="string">
    <enumeration value="MWh" />
  </restriction>
</simpleType>

<simpleType name="tyTransactionType">
  <restriction base="string">
    <enumeration value="TransactionTimmFA" />
    <enumeration value="tyError" />
    <enumeration value="TransactionContratto" />
    <enumeration value="TransactionItemContratto" />
    <enumeration value="TransactionQuoteCapacita" />
  </restriction>
</simpleType>

<simpleType name="tyReasonType">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="32" />
  </restriction>
</simpleType>
```

## PDE: IMPLEMENTATION GUIDE

```
<simpleType name="tyReasonTextType">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="1024" />
  </restriction>
</simpleType>
<simpleType name="yesNoType">
  <restriction base="string">
    <enumeration value="Yes"/>
    <enumeration value="No"/>
  </restriction>
</simpleType>

<simpleType name="tyMPN">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="32" />
  </restriction>
</simpleType>

<simpleType name="marketType">
  <restriction base="string">
    <enumeration value="MGP"/>
    <enumeration value="MA1"/>
    <enumeration value="MB"/>
    <enumeration value="MSD"/>
  </restriction>
</simpleType>

<simpleType name="tyTipoOperazione">
  <restriction base="string">
    <enumeration value="AddNew"/>
    <enumeration value="Modify"/>
  </restriction>
</simpleType>

  <simpleType name="tyTipoOperazione2">
    <restriction base="string">
      <enumeration value="AddNew"/>
      <enumeration value="DeleteInsert"/>
    </restriction>
  </simpleType>
</schema>
```



### 3 TRANSAZIONI XML SOTTOMESSE DAGLI OPERATORI A PDE

#### 3.1 Contratto

```
<?xml version='1.0' encoding='ISO-8859-1'?>
<Message
  xmlns:xsd='http://www.w3.org/2001/XMLSchema'
  xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
  MessageDate='2009-03-11'
  xmlns='urn:XML-TIMM'
  MessageType='Request' >
  <Header>
    <Sender>
      <OperatorMsgCode>OEXXXX</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <Contratto>
      <ContrattoCommon>
        <CodiceContratto>XX-XX-XXXXZ</CodiceContratto>
        <DataStipula>20090201</DataStipula>
        <Cedente>OEXXXX</Cedente>
        <RagioneSocialeCedente>Operatore elettrico1 SPA</RagioneSocialeCedente>
        <Acquirente>OEYYYY</Acquirente>
        <RagioneSocialeAcquirente>Operatore elettrico2 SPA</RagioneSocialeAcquirente>
        <ControparteElettrica>true</ControparteElettrica>
        <Tipologia>OTC</Tipologia>
        <MercatoOrganizzato>MKT1</MercatoOrganizzato>
        <Struttura>altro</Struttura>
        <Descrizione>campo descrizione</Descrizione>
        <Indicizzato>>false</Indicizzato>
        <Indicizzazione>campo descrizione indicizzazione</Indicizzazione>
        <ProfiloGiornaliero Data='20090401'>
          <ProfiloOrario Ora='1' Prezzo='12'>33,75</ProfiloOrario>
        </ProfiloGiornaliero>
      </ContrattoCommon>
    </Contratto>
  </Transaction>
</Message>
```

## PDE: IMPLEMENATATION GUIDE

```
<ProfiloOrario Ora='2' Prezzo='14'>33,76</ProfiloOrario>
<ProfiloOrario Ora='3' Prezzo='16'>33,77</ProfiloOrario>
<ProfiloOrario Ora='4' Prezzo='18'>33,78</ProfiloOrario>
<ProfiloOrario Ora='5' Prezzo='20'>33,79</ProfiloOrario>
<ProfiloOrario Ora='6' Prezzo='22'>33,8</ProfiloOrario>
<ProfiloOrario Ora='7' Prezzo='24'>33,81</ProfiloOrario>
<ProfiloOrario Ora='8' Prezzo='26'>33,82</ProfiloOrario>
<ProfiloOrario Ora='9' Prezzo='28'>33,83</ProfiloOrario>
<ProfiloOrario Ora='10' Prezzo='30'>33,84</ProfiloOrario>
<ProfiloOrario Ora='11' Prezzo='32'>33,85</ProfiloOrario>
<ProfiloOrario Ora='12' Prezzo='34'>33,86</ProfiloOrario>
<ProfiloOrario Ora='13' Prezzo='36'>33,87</ProfiloOrario>
<ProfiloOrario Ora='14' Prezzo='38'>33,88</ProfiloOrario>
<ProfiloOrario Ora='15' Prezzo='40'>33,89</ProfiloOrario>
<ProfiloOrario Ora='16' Prezzo='42'>33,9</ProfiloOrario>
<ProfiloOrario Ora='17' Prezzo='44'>33,91</ProfiloOrario>
<ProfiloOrario Ora='18' Prezzo='46'>33,92</ProfiloOrario>
<ProfiloOrario Ora='19' Prezzo='48'>33,93</ProfiloOrario>
<ProfiloOrario Ora='20' Prezzo='50'>33,94</ProfiloOrario>
<ProfiloOrario Ora='21' Prezzo='52'>33,95</ProfiloOrario>
<ProfiloOrario Ora='22' Prezzo='54'>33,96</ProfiloOrario>
<ProfiloOrario Ora='23' Prezzo='56'>33,97</ProfiloOrario>
<ProfiloOrario Ora='24' Prezzo='58'>33,98</ProfiloOrario>
</ProfiloGiornaliero>
<ProfiloGiornaliero Data='20090402'>
  <ProfiloOrario Ora='1' Prezzo='12'>57</ProfiloOrario>
  <ProfiloOrario Ora='2' Prezzo='14'>33,76</ProfiloOrario>
  <ProfiloOrario Ora='3' Prezzo='16'>33,77</ProfiloOrario>
  <ProfiloOrario Ora='4' Prezzo='18'>33,78</ProfiloOrario>
  <ProfiloOrario Ora='5' Prezzo='20'>33,79</ProfiloOrario>
  <ProfiloOrario Ora='6' Prezzo='22'>33,8</ProfiloOrario>
  <ProfiloOrario Ora='7' Prezzo='24'>33,81</ProfiloOrario>
  <ProfiloOrario Ora='8' Prezzo='26'>33,82</ProfiloOrario>
  <ProfiloOrario Ora='9' Prezzo='28'>33,83</ProfiloOrario>
  <ProfiloOrario Ora='10' Prezzo='30'>33,84</ProfiloOrario>
  <ProfiloOrario Ora='11' Prezzo='32'>33,85</ProfiloOrario>
  <ProfiloOrario Ora='12' Prezzo='34'>33,86</ProfiloOrario>
  <ProfiloOrario Ora='13' Prezzo='36'>33,87</ProfiloOrario>
  <ProfiloOrario Ora='14' Prezzo='38'>33,88</ProfiloOrario>
  <ProfiloOrario Ora='15' Prezzo='40'>33,89</ProfiloOrario>
  <ProfiloOrario Ora='16' Prezzo='42'>33,9</ProfiloOrario>
  <ProfiloOrario Ora='17' Prezzo='44'>33,91</ProfiloOrario>
```

**PDE: IMPLEMENTATION GUIDE**

```
<ProfiloOrario Ora='18' Prezzo='46'>33,92</ProfiloOrario>  
<ProfiloOrario Ora='19' Prezzo='48'>33,93</ProfiloOrario>  
<ProfiloOrario Ora='20' Prezzo='50'>33,94</ProfiloOrario>  
<ProfiloOrario Ora='21' Prezzo='52'>33,95</ProfiloOrario>  
<ProfiloOrario Ora='22' Prezzo='54'>33,96</ProfiloOrario>  
<ProfiloOrario Ora='23' Prezzo='56'>33,97</ProfiloOrario>  
<ProfiloOrario Ora='24' Prezzo='58'>33,98</ProfiloOrario>  
  </ProfiloGiornaliero>  
  </ContrattoCommon>  
</Contratto>  
</Transaction>  
</Message>
```

## 3.1.1 Contratto.xsd

```

<?xml version="1.0" encoding="ISO-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema" targetNamespace="urn:XML-TIMM" xmlns:pd="urn:XML-TIMM" elementFormDefault="qualified">
  <include schemaLocation="RegistrationTypes.xsd" />
  <include schemaLocation="Types.xsd" />
  <complexType name="tyContrattoCommon">
    <sequence>
      <element name="CodiceContratto" type="pd:tyCodiceContratto" minOccurs="1" maxOccurs="1" />
      <element name="DataStipula" type="pd:tyDate" minOccurs="0" maxOccurs="1" />
      <element name="Cedente" type="pd:tyCedenteAcquirente" minOccurs="1" maxOccurs="1" />
      <element name="RagioneSocialeCedente" type="pd:tyRagioneSociale" minOccurs="0" maxOccurs="1" />
      <element name="Acquirente" type="pd:tyCedenteAcquirente" minOccurs="1" maxOccurs="1" />
      <element name="RagioneSocialeAcquirente" type="pd:tyRagioneSociale" minOccurs="0" maxOccurs="1" />
      <element name="ControparteElettrica" type="boolean" minOccurs="1" maxOccurs="1" />
      <element name="Tipologia" type="pd:tyTipologiaContratto" minOccurs="1" maxOccurs="1" />
      <element name="MercatoOrganizzato" type="pd:tyMercatoOrganizzato" minOccurs="0" maxOccurs="1" />
      <element name="Struttura" type="pd:tyStrutturaContratto" minOccurs="1" maxOccurs="1" />
      <element name="Descrizione" type="pd:tyDescrizioneContratto" minOccurs="0" maxOccurs="1" />
      <element name="Indicizzato" type="boolean" minOccurs="1" maxOccurs="1" />
      <element name="Indicizzazione" type="pd:tyIndicizzazioneContratto" minOccurs="0" maxOccurs="1" />
      <element name="Premio" type="pd:tyPrice" minOccurs="0" maxOccurs="1" />
      <element name="ProfiloGiornaliero" type="pd:ProfiloGiornaliero" minOccurs="1" maxOccurs="unbounded" />
    </sequence>
  </complexType>
  <complexType name="ProfiloGiornaliero">
    <sequence>
      <element name="ProfiloOrario" type="pd:ProfiloOrario" minOccurs="1" maxOccurs="25" />
    </sequence>
  <attribute name="Data" type="pd:tyDate" use="required" />
</complexType>
<complexType name="ProfiloOrario">
  <simpleContent>
    <extension base="pd:tyQtyMWh">
      <attribute name="Ora" type="pd:tyHourIntervalType" use="required" />
      <attribute name="Prezzo" type="pd:tyPrice" use="optional" />
    </extension>
  </simpleContent>
</complexType>
</schema>

```

### 3.2 ItemContratto

```
<?xml version='1.0' encoding='ISO-8859-1'?>
<Message
  xmlns:xsd='http://www.w3.org/2001/XMLSchema'
  xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
  MessageDate='2009-03-26'
  xmlns='urn:XML-TIMM'
  MessageType='Request'>
  <Header>
    <Sender>
      <OperatorMsgCode>OEXXXX</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <ItemContratto>
      <ItemContrattoCommon>
        <CodiceContratto>XX-XX-XXXX</CodiceContratto>
        <ProfiloGiornaliero Data='20070430'>
          <ProfiloOrario Ora='1' Prezzo='12'>33,75</ProfiloOrario>
          <ProfiloOrario Ora='2' Prezzo='14'>33,76</ProfiloOrario>
          <ProfiloOrario Ora='3' Prezzo='16'>33,77</ProfiloOrario>
          <ProfiloOrario Ora='4' Prezzo='18'>33,78</ProfiloOrario>
          <ProfiloOrario Ora='5' Prezzo='20'>33,79</ProfiloOrario>
          <ProfiloOrario Ora='6' Prezzo='22'>33,8</ProfiloOrario>
          <ProfiloOrario Ora='7' Prezzo='24'>33,81</ProfiloOrario>
          <ProfiloOrario Ora='8' Prezzo='26'>33,82</ProfiloOrario>
          <ProfiloOrario Ora='9' Prezzo='28'>33,83</ProfiloOrario>
          <ProfiloOrario Ora='10' Prezzo='30'>33,84</ProfiloOrario>
          <ProfiloOrario Ora='11' Prezzo='32'>33,85</ProfiloOrario>
          <ProfiloOrario Ora='12' Prezzo='34'>33,86</ProfiloOrario>
          <ProfiloOrario Ora='13' Prezzo='36'>33,87</ProfiloOrario>
          <ProfiloOrario Ora='14' Prezzo='38'>33,88</ProfiloOrario>
          <ProfiloOrario Ora='15' Prezzo='40'>33,89</ProfiloOrario>
          <ProfiloOrario Ora='16' Prezzo='42'>33,9</ProfiloOrario>
          <ProfiloOrario Ora='17' Prezzo='44'>33,91</ProfiloOrario>
          <ProfiloOrario Ora='18' Prezzo='46'>33,92</ProfiloOrario>
        </ProfiloGiornaliero>
      </ItemContrattoCommon>
    </ItemContratto>
  </Transaction>
</Message>
```

## PDE: IMPLEMENTATION GUIDE

```
<ProfiloOrario Ora='19' Prezzo='48'>33,93</ProfiloOrario>
<ProfiloOrario Ora='20' Prezzo='50'>33,94</ProfiloOrario>
<ProfiloOrario Ora='21' Prezzo='52'>33,95</ProfiloOrario>
<ProfiloOrario Ora='22' Prezzo='54'>33,96</ProfiloOrario>
<ProfiloOrario Ora='23' Prezzo='56'>33,97</ProfiloOrario>
<ProfiloOrario Ora='24' Prezzo='58'>33,98</ProfiloOrario>
</ProfiloGiornaliero>
<ProfiloGiornaliero Data='20070501'>
  <ProfiloOrario Ora='1' Prezzo='12'>57</ProfiloOrario>
  <ProfiloOrario Ora='2' Prezzo='14'>33,76</ProfiloOrario>
  <ProfiloOrario Ora='3' Prezzo='16'>33,77</ProfiloOrario>
  <ProfiloOrario Ora='4' Prezzo='18'>33,78</ProfiloOrario>
  <ProfiloOrario Ora='5' Prezzo='20'>33,79</ProfiloOrario>
  <ProfiloOrario Ora='6' Prezzo='22'>33,8</ProfiloOrario>
  <ProfiloOrario Ora='7' Prezzo='24'>33,81</ProfiloOrario>
  <ProfiloOrario Ora='8' Prezzo='26'>33,82</ProfiloOrario>
  <ProfiloOrario Ora='9' Prezzo='28'>33,83</ProfiloOrario>
  <ProfiloOrario Ora='10' Prezzo='30'>33,84</ProfiloOrario>
  <ProfiloOrario Ora='11' Prezzo='32'>33,85</ProfiloOrario>
  <ProfiloOrario Ora='12' Prezzo='34'>33,86</ProfiloOrario>
  <ProfiloOrario Ora='13' Prezzo='36'>33,87</ProfiloOrario>
  <ProfiloOrario Ora='14' Prezzo='38'>33,88</ProfiloOrario>
  <ProfiloOrario Ora='15' Prezzo='40'>33,89</ProfiloOrario>
  <ProfiloOrario Ora='16' Prezzo='42'>33,9</ProfiloOrario>
  <ProfiloOrario Ora='17' Prezzo='44'>33,91</ProfiloOrario>
  <ProfiloOrario Ora='18' Prezzo='46'>33,92</ProfiloOrario>
  <ProfiloOrario Ora='19' Prezzo='48'>33,93</ProfiloOrario>
  <ProfiloOrario Ora='20' Prezzo='50'>33,94</ProfiloOrario>
  <ProfiloOrario Ora='21' Prezzo='52'>33,95</ProfiloOrario>
  <ProfiloOrario Ora='22' Prezzo='54'>33,96</ProfiloOrario>
  <ProfiloOrario Ora='23' Prezzo='56'>33,97</ProfiloOrario>
  <ProfiloOrario Ora='24' Prezzo='58'>33,98</ProfiloOrario>
</ProfiloGiornaliero>
</ItemContrattoCommon>
</ItemContratto>
</Transaction>
</Message>
```

### 3.2.1 ItemContratto.xsd

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema" targetNamespace="urn:XML-TIMM" xmlns:pd="urn:XML-TIMM" elementFormDefault="qualified">
  <include schemaLocation="RegistrationTypes.xsd" />
  <include schemaLocation="Types.xsd" />
  <complexType name="tyItemContrattoCommon">
    <sequence>
      <element name="CodiceContratto" type="pd:tyCodiceContratto" minOccurs="1" maxOccurs="1" />
    </sequence>
  </complexType>
  <complexType name="ProfiloGiornalieroItem">
    <sequence>
      <element name="ProfiloGiornaliero" type="pd:ProfiloGiornalieroItem" minOccurs="1" maxOccurs="unbounded" />
    </sequence>
  </complexType>
  <complexType name="ProfiloOrarioItem">
    <sequence>
      <element name="ProfiloOrario" type="pd:ProfiloOrarioItem" minOccurs="1" maxOccurs="25" />
    </sequence>
  </complexType>
  <attribute name="Data" type="pd:tyDate" use="required" />
  </complexType>
  <complexType name="ProfiloOrarioItem">
    <simpleContent>
      <extension base="pd:tyQtyMWh">
        <attribute name="Ora" type="pd:tyHourIntervalType" use="required" />
        <attribute name="Prezzo" type="pd:tyPrice" use="optional" />
      </extension>
    </simpleContent>
  </complexType>
</schema>
```

### 3.3 QuoteCapacita

```
<?xml version='1.0' encoding='ISO-8859-1'?>
<Message
  xmlns:xsd='http://www.w3.org/2001/XMLSchema'
  xmlns:xsi='http://www.w3.org/2001/XMLSchema-instance'
  MessageDate='2009-03-25'
  xmlns='urn:XML-TIMM'
  MessageType='Request' >
  <Header>
    <Sender>
      <OperatorMsgCode>OEXXXXX</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <QuoteCapacita>
      <QuoteCapacitaCommon>
        <CodiceUnita>UP_AMXXXX_1</CodiceUnita>
        <CodiceOperatore>OEXXXXX</CodiceOperatore>
        <QuoteCapacitaGiornaliera Data='20090502' >
          <QuoteCapacitaOraria Ora='1'>0,4</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='2'>0,5</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='3'>0,6</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='4'>0,7</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='5'>0,8</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='6'>0,9</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='7'>0,1</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='8'>0,11</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='9'>0,12</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='10'>0,13</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='11'>0,14</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='12'>0,15</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='13'>0,16</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='14'>0,17</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='15'>0,18</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='16'>0,19</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='17'>0,2</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='18'>0,21</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='19'>0,22</QuoteCapacitaOraria>
          <QuoteCapacitaOraria Ora='20'>0,23</QuoteCapacitaOraria>
        </QuoteCapacitaGiornaliera >
      </QuoteCapacitaCommon>
    </QuoteCapacita>
  </Transaction>
</Message>
```



## PDE: IMPLEMENATATION GUIDE

```
<QuoteCapacitaOraria Ora='21'>0,24</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='22'>0,25</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='23'>0,26</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='24'>0,27</QuoteCapacitaOraria>
</QuoteCapacitaGiornaliera>
<QuoteCapacitaGiornaliera Data='20090503'>
  <QuoteCapacitaOraria Ora='1'>0,8</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='2'>0,5</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='3'>0,6</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='4'>0,7</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='5'>0,8</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='6'>0,9</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='7'>0,1</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='8'>0,11</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='9'>0,12</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='10'>0,13</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='11'>0,14</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='12'>0,15</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='13'>0,16</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='14'>0,17</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='15'>0,18</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='16'>0,19</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='17'>0,2</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='18'>0,21</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='19'>0,22</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='20'>0,23</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='21'>0,24</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='22'>0,25</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='23'>0,26</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='24'>0,27</QuoteCapacitaOraria>
</QuoteCapacitaGiornaliera>
</QuoteCapacitaCommon>
</QuoteCapacita>
</Transaction>
<Transaction>
  <QuoteCapacita>
    <QuoteCapacitaCommon>
      <CodiceUnita>UP_YYYYY_1</CodiceUnita>
      <CodiceOperatore>OEXXXXX</CodiceOperatore>
      <QuoteCapacitaGiornaliera Data='20090504'>
        <QuoteCapacitaOraria Ora='1'>0,41</QuoteCapacitaOraria>
        <QuoteCapacitaOraria Ora='2'>0,46</QuoteCapacitaOraria>
        <QuoteCapacitaOraria Ora='3'>0,6</QuoteCapacitaOraria>
        <QuoteCapacitaOraria Ora='4'>0,7</QuoteCapacitaOraria>
        <QuoteCapacitaOraria Ora='5'>0,8</QuoteCapacitaOraria>
        <QuoteCapacitaOraria Ora='6'>0,9</QuoteCapacitaOraria>
```

## PDE: IMPLEMENTATION GUIDE

```
<QuoteCapacitaOraria Ora='7'>0,1</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='8'>0,11</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='9'>0,12</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='10'>0,13</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='11'>0,14</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='12'>0,15</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='13'>0,16</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='14'>0,17</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='15'>0,18</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='16'>0,19</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='17'>0,2</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='18'>0,21</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='19'>0,22</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='20'>0,23</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='21'>0,24</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='22'>0,25</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='23'>0,26</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='24'>0,27</QuoteCapacitaOraria>
</QuoteCapacitaGiornaliera>
<QuoteCapacitaGiornaliera Data='20090505'>
  <QuoteCapacitaOraria Ora='1'>0,81</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='2'>0,5</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='3'>0,6</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='4'>0,7</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='5'>0,8</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='6'>0,9</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='7'>0,1</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='8'>0,11</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='9'>0,12</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='10'>0,13</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='11'>0,14</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='12'>0,15</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='13'>0,16</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='14'>0,17</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='15'>0,18</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='16'>0,19</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='17'>0,2</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='18'>0,21</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='19'>0,22</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='20'>0,23</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='21'>0,24</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='22'>0,25</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='23'>0,26</QuoteCapacitaOraria>
  <QuoteCapacitaOraria Ora='24'>0,27</QuoteCapacitaOraria>
</QuoteCapacitaGiornaliera>
<QuoteCapacitaGiornaliera Data='20090506'>
  <QuoteCapacitaOraria Ora='1'>0,87</QuoteCapacitaOraria>
```

## PDE: IMPLEMENTATION GUIDE

```
<QuoteCapacitaOraria Ora='2'>0,5</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='3'>0,6</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='4'>0,7</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='5'>0,8</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='6'>0,9</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='7'>0,1</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='8'>0,11</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='9'>0,12</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='10'>0,13</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='11'>0,14</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='12'>0,15</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='13'>0,16</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='14'>0,17</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='15'>0,18</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='16'>0,19</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='17'>0,2</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='18'>0,21</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='19'>0,22</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='20'>0,23</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='21'>0,24</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='22'>0,25</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='23'>0,26</QuoteCapacitaOraria>
<QuoteCapacitaOraria Ora='24'>0,27</QuoteCapacitaOraria>
</QuoteCapacitaGiornaliera>
</QuoteCapacitaCommon>
</QuoteCapacita>
</Transaction>
</Message>
```

### 3.3.1 QuoteCapacita.xsd

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema" targetNamespace="urn:XML-TIMM" xmlns:pd="urn:XML-TIMM" elementFormDefault="qualified">
  <include schemaLocation="RegistrationTypes.xsd" />
  <include schemaLocation="Types.xsd" />
  <complexType name="tyQuoteCapacitaCommon">
    <sequence>
      <element name="CodiceUnita" type="pd:tyCodiceUnita" minOccurs="1" maxOccurs="1" />
      <element name="CodiceOperatore" type="pd:tyCodiceoperatore" minOccurs="1" maxOccurs="1" />
      <element name="QuoteCapacitaGiornaliera" type="pd:QuoteCapacitaGiornaliera" minOccurs="1" maxOccurs="unbounded" />
    </sequence>
  </complexType>
  <complexType name="QuoteCapacitaGiornaliera">
    <sequence>
      <element name="QuoteCapacitaOraria" type="pd:QuoteCapacitaOraria" minOccurs="1" maxOccurs="25" />
    </sequence>
  <attribute name="Data" type="pd:tyDate" use="required" />
</complexType>
<complexType name="QuoteCapacitaOraria">
  <simpleContent>
    <extension base="pd:tyAlpha">
      <attribute name="Ora" type="pd:tyHourIntervalType" use="required" />
    </extension>
  </simpleContent>
</complexType>
</schema>
```

## 4 TRANSAZIONI XML MESSE A DISPOSIZIONE DEGLI OPERATORI

### 4.1 FunctionalAcknowledgement

#### 4.1.1 Functional Acknowledgement Positivo

```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
MessageTypes="Response" MessageDate="2009-03-25" MessageTime="10:48:49.8281250+01:00"
ResponseReferenceMessageCode="814" ResponseMessageStatus="Accepted" xmlns="urn:XML-TIMM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>OEXXXX</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <TimmFA>
      <FunctionalAcknowledgement TransactionType="TransactionQuoteCapacita" Status="Accepted" XmlOrder="1" />
    </TimmFA>
  </Transaction>
  <Transaction>
    <TimmFA>
      <FunctionalAcknowledgement TransactionType="TransactionQuoteCapacita" Status="Accepted" XmlOrder="2" />
    </TimmFA>
  </Transaction>
</Message>
```

#### 4.1.2 Functional Acknowledgement Negative

```

<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
MessageTypes="Response" MessageDate="2009-03-25" MessageTime="10:47:18.750000+01:00"
ResponseReferenceMessageCode="812" ResponseMessageStatus="Rejected" xmlns="urn:XML-TIMM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>OEAESRL</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <TimmFA>
      <FunctionalAcknowledgement TransactionType="TransactionQuoteCapacita" Status="Rejected" XmlOrder="1">
        <RejectInformation>
          <Reason>QC05</Reason>
          <ReasonText>la quota alfa per la data 02/03/2009 deve essere comunicata entro 01/03/2009 12.00.00
(data corrente: 25/03/2009 10.47.17)</ReasonText>
        </RejectInformation>
      </FunctionalAcknowledgement>
    </TimmFA>
  </Transaction>
  <Transaction>
    <TimmFA>
      <FunctionalAcknowledgement TransactionType="TransactionQuoteCapacita" Status="Rejected" XmlOrder="2">
        <RejectInformation>
          <Reason>QC05</Reason>
          <ReasonText>la quota alfa per la data 04/03/2009 deve essere comunicata entro 03/03/2009 12.00.00
(data corrente: 25/03/2009 10.47.17)</ReasonText>
        </RejectInformation>
      </FunctionalAcknowledgement>
    </TimmFA>
  </Transaction>
</Message>

```


### 4.1.3 FunctionalAcknowledgement.xsd

```
<?xml version="1.0" encoding="iso-8859-1" ?>
<schema
  xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-TIMM"
  xmlns:pd="urn:XML-TIMM"
  elementFormDefault="qualified">
  <include schemaLocation="RegistrationTypes.xsd" />
  <include schemaLocation="BaseMessageTypes.xsd" />
  <include schemaLocation="Types.xsd" />
  <complexType name="tyFunctionalAcknowledgement">
    <sequence>
      <element ref="pd:RejectInformation" minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
    <attribute name="TransactionType" type="pd:tyTransactionType" use="optional"/>
    <attribute name="Status" type="pd:tyTransactionStatus" use="required"/>
    <attribute name="MPN" type="string" use="optional"/>
    <attribute name="XmlOrder" type="int" use="required"/>
  </complexType>
</schema>
```

## 4.2 Notifica di errore (ref xsd: TimmBaseMessage.xsd)

```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
MessageDate="2009-03-25" MessageTime="10:44:25.1406250+01:00" ResponseReferenceMessageCode="809"
ResponseMessageStatus="Rejected" xmlns="urn:XML-TIMM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDAU</OperatorMsgCode>
    </Receiver>
  </Header>
  <Error Code="M01" Description="The 'Ora' attribute is invalid - The value '' is invalid according to its
datatype 'urn:XML-TIMM:tyHourIntervalType' - The string '' is not a valid Integer value." />
</Message>
```





	Description	Possible Values
<b>Element / Attribute Name</b>	The name of the Element or Attribute used in the XML file	N/A
<b>Attribute / Element</b>	Whether a field is an Attribute or an Element within the XML document	A = Attribute E = Element
<b>Valid Information in Field (enumeration)</b>	Validation rules for element or attribute value, including list of possible values in enumeration	
<b>Data Type</b>	Describes the type of data expected in the field	A/N= <u>A</u> lpha <u>N</u> umeric (Field allows for alphabetic values, numeric values, as well as any combination of alphabetic and numeric values) N= Numeric (integers only) N/A= <u>N</u> ot <u>A</u> pplicable Enum= The only valid values are listed. Date= Date format used. Bool = boolean Decimal= Illustrates the position of the decimal point in reference to the overall length of the field.
<b>Occurances Min/Max</b>	Describes the expected number of times that the attribute or element can occur within the XML document	n/x where n= the minimum number of occurrences allowed for the element or attribute and x = the maximum number of occurrences for the element or attribute; or a specification directly of the number of occurrences within another structure, such as "1 per PIPEDocument".
<b>Field Length</b>	The expected length of the field	either a number which represents the required number of characters, or max=nn, where nn is the maximum number of digits or characters allowed for the field N/A= <u>N</u> ot <u>A</u> pplicable
<b>Definition</b>	The explanation of the Element or Attribute	N/A

## Contratto Implementation Guide for PDE

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>		N/A	N/A	1 for file	N/A	
xmlns:xsd	A		A/N	1/1		Associates the actual schema instance being used to the name space.
xmlns:xsi	A		A/N	1/1		Defines the schema instance being used.
Version	E	1.0.2.0	A/N		max=7	Identifies the version of the CeMessageSchema
Header	E	(see Header data structure)		1/1		Sender and recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
MessageCode	A		A/N	0/1	min=1. max=32	Message identifier
MessageType	A	Request	Enum	0/1		Message Type
MessageDate	A	Valid Date (YYYY-MM-DD)	Date	1/1		Date of the message
MessageTime	A	Valid Time (hh:mm:ss.ffffff+01:00)	Time	0/1		Time of the message
MessageSubject	A		Enum	0/1		identifies the type of the transaction inside the message
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	min=1 max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	(IDGME)	A/N	1/1	min=1 max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who receives
<b>Transaction</b>						
Contratto	E	(see Contratto data structure)		1/1		
MPN	A		A/N	0/1	max=32	identifier for the transaction assigned by the Operator
<b>Contratto</b>						
ContrattoCommon	E	(see ContrattoCommon data structure)		1/1		
<b>ContrattoCommon</b>						
CodiceContratto	E		A/N	1/1	min=1 max=32	Contratto unique identifier
DataStipula	E	valid date (YYYYMMDD)	Date	1/1	decimal(8,0)	Contratto's date of conclusion
Cedente	E		A/N	1/1	min=1 max=150	Seller's ETSO code (only for electricity operators)/ VAT
RagioneSocialeCedente	E		A/N	0/1	max=256	Seller's name
Acquirente	E		A/N	1/1	min=1 max=150	Buyer's ETSO code (only for electricity operators)/ VAT
RagioneSocialeAcquirente	E		A/N	0/1	max=256	Buyer's name
ControparteElettrica	E	true,false	Bool	1/1	bool	type of counterparty
Tipologia	E	OTC,MKT	Enum	1/1		OTC (over the counter), MKT (organized market)
MercatoOrganizzato	E		A/N	0/1	min=0 max=256	organized market's code
Struttura	E	futere, swap, opzione, altro	Enum	1/1		structure of the contract
Descrizione	E		A/N	0/1	min=0 max=256	description of the structure if the Struttura is "altro"
Indicizzato	E	true,false	Bool	1/1		indicates whether the contract is indexed
Indicizzazione	E		A/N	0/1	min=0 max=256	description of the indexing if the Indicizzato is true
Premio	E	999999999999.99	Decimal	0/1		Award of contract
ProfiloGiornaliero	E	(see ProfiloGiornaliero structure)		1 or more		
<b>ProfiloGiornaliero</b>						
ProfiloOrario	E	(see ProfiloOrario structure)		1 to 25		
Data	A	valid date (YYYYMMDD)	Date	1/1		Date
<b>ProfiloOrario</b>						
Ora	A	999999999999.99	Decimal		(18,3)	Quantity
Prezzo	A		N	1/1	min=1 max=25	Hour
	A	999999999999.99	Decimal	0/1	(18,2)	Price

## ItemContratto Implementation Guide for PDE

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		N/A	N/A	1 for file	N/A	
xmlns:xsd	A		A/N	1/1		Associates the actual schema instance being used to the name space.
xmlns:xsi	A		A/N	1/1		Defines the schema instance being used.
Version	E	1.0.2.0	A/N		max=7	Identifies the version of the CeMessageSchema
Header	E	(see Header data structure)		1/1		Sender and recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
MessageCode	A		A/N	0/1	min=1. max=32	Message identifier
MessageType	A	Request	Enum	0/1		Message Type
MessageDate	A	Valid Date (YYYY-MM-DD)	Date	1/1		Date of the message
MessageTime	A	ValidTime (hh:mm:ss.ffffff+01:00)	Time	0/1		Time of the message
MessageSubject	A		Enum	0/1		identifies the type of the transaction inside the message
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	min=1 max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	(IDGME)	A/N	1/1	min=1 max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who receives
<b>Transaction</b>						
ItemContratto	E	(see ItemContratto data structure)		1/1		
MPN	A		A/N	0/1	max=32	identifier for the transaction assigned by the Operator
<b>ItemContratto</b>						
ContrattoCommon	E	(see ItemContrattoCommon data structure)		1/1		
<b>ItemContrattoCommon</b>						
CodiceContratto	E		A/N	1/1	min=1 max=32	Contratto unique identifier
ProfiloGiornaliero	E	(see ProfiloGiornaliero structure)		1 or more		
<b>ProfiloGiornaliero</b>						
ProfiloOrario	E	(see ProfiloOrario structure)		1 to 25		
Data	A	valid date (YYYYMMDD)	Date	1/1		Date
<b>ProfiloOrario</b>						
Ora	A	999999999999.99	N	1/1	min=1 max=25	Hour
Prezzo	A	999999999999.99	Decimal	0/1	(18,2)	Price

## QuoteCapacita Implementation Guide for PDE

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		N/A	N/A	1 for file	N/A	
xmlns:xsd	A		A/N	1/1		Associates the actual schema instance being used to the name space.
xmlns:xsi	A		A/N	1/1		Defines the schema instance being used.
Version	E	1.0.2.0	A/N		max=7	Identifies the version of the CeMessageSchema
Header	E	(see Header data structure)		1/1		Sender and recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
MessageCode	A		A/N	0/1	min=1. max=32	Message identifier
MessageType	A	Request	Enum	0/1		Message Type
MessageDate	A	Valid Date (YYYY-MM-DD)	Date	1/1		Date of the message
MessageTime	A	ValidTime (hh:mm:ss.ffffff+01:00)	Time	0/1		Time of the message
MessageSubject	A		Enum	0/1		identifies the type of the transaction inside the message
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	min=1 max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	(IDGME)	A/N	1/1	min=1 max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who receives
<b>Transaction</b>						
ItemContratto	E	(see ItemContratto data structure)		1/1		
MPN	A		A/N	0/1	max=32	identifier for the transaction assigned by the Operator
<b>QuoteCapacita</b>						
QuoteCapacitaCommon	E	(see QuoteCapacitaCommon data structure)		1/1		
<b>QuoteCapacitaCommon</b>						
CodiceUnita	E		A/N	1/1	min=1 max=16	Alphanumeric code identifying the Consumption or Production Unit
CodiceOperatore	E			1/1	min=1 max=16	Operator's ETSO code
QuoteCapacitaGionraliera	E	(see QuoteCapacitaGionraliera structure)		1 or more		
<b>QuoteCapacitaGionraliera</b>						
QuoteCapacitaOraria	E	(see QuoteCapacitaOraria structure)		1 to 25		
Data	A	valid date (YYYYMMDD)	Date	1/1		Date
<b>QuoteCapacitaOraria</b>						
Ora	A	(0~1 (es: 0,8))	Decimal	1/1	(3,2)	Hour

## FA Implementation Guide for PDE

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		N/A	N/A	1 for file	N/A	
xmains.xsd	A		A/N	1/1		Associates the actual schema instance being used to the name space.
xmains.xsi	A		A/N	1/1		Defines the schema instance being used.
Header	E	(see Header data structure)		1/1		Sender and recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
MessageType	A	Response		0/1		Message Type
MessageDate	A	Valid Date (YYYY-MM-DD)	Date	1/1		Date of the message
MessageTime	A	ValidTime (hh:mm:ss.ffffff+01:00)	Time	0/1		Time of the message
ResponseReferenceMessageCode	A					Indicates the ID of message that is being referred to
ResponseMessageStatus	A		Accepted/Rejected/PartiallyAccepted	1/1		In the FunctionalAcknowledgment transaction indicates: 1. If the document is accepted (Accept) which means that all the transactions in the document have passed validation, partially accepted (Partial) which means that at least one transaction has been rejected, or rejected (Reject) which means that all the transaction have been rejected. 2. That a single transaction has been accepted or rejected.
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E	(IDGME)	A/N	1/1	min=1 max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E		A/N	1/1	min=1 max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who receives
<b>Transaction</b>						
TransactionCode	A		A/N	0/1	max=32	unique identifier of the transaction
TimmFA	E	(see TimmFA structure)		1/1		
<b>TimmFA</b>						
FunctionalAcknowledgement	E	(see FunctionalAcknowledgement structure)		1/1		Contains tags that define the positive or negative acknowledgement of receipt of the original transaction.
<b>FunctionalAcknowledgement</b>						
TransactionType	A	ENUM	A/N	0/1		Indicates the type of transaction that is being referred to.
Status	A	Accept or Reject	A/N	1/1		
XmlOrder	A		A/N	1/1	int	original order in message that is being referred to
RejectInformation	E	(see Reject Information data structure)	A/N	0 or more		
<b>RejectInformation</b>						
Reason	E	N/A	A/N	1/1	max=30	A short description of the rejection of the transaction
ReasonText	E	N/A	A/N	1/1	max=250	The text explanation for the rejection of the transaction

### ERROR Implementation Guide for PDE

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>		N/A	N/A	1 for file	N/A	
xmains.xsd	A		A/N	1/1		Associates the actual schema instance being used to the name space.
xmains.xsi	A		A/N	1/1		Defines the schema instance being used.
Header	E	(see Header data structure)		1/1		Sender and recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
MessageType	A	Response		0/1		Message Type
MessageDate	A	Valid Date (YYYY-MM-DD)	Date	1/1		Date of the message
MessageTime	A	ValidTime (hh:mm:ss.ffffff+01:00)	Time	0/1		Time of the message
ResponseReferenceMessageCode	A					Indicates the ID of message that is being referred to
ResponseMessageStatus	A		Rejected	1/1		
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E	(IDGME)	A/N	1/1	min=1 max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E		A/N	1/1	min=1 max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	min=1 max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	min=1 max=16	The unique identifier for the user who receives
<b>Error</b>				1/1		
Code	A		A/N	0/1	max=30	A short description of the rejection of the message
Description	E	(see TimmFA structure)		1/1	max=250	The text explanation for the rejection of the message